


CRJ Rail

Cable Size 3/64" - 1/16" 1.2 - 1.5 mm	
Maximum Weight 3/64": 40 lbs. 18 kg 1/16": 65 lbs. 30 kg	
Function wall-mounted rail system	



Arakawa Hanging Systems, Inc.
 2505 SE 11th Ave, Suite 122
 Portland, OR 97202
 phone: 503.236.0440
 fax: 503.236.0427
 toll free: 888.272.5292
www.arakawagrip.com

The CRJ rail is Arakawa's moderate weight wall railing system. Arakawa rail clips attach to the rail at any location and can be moved horizontally along the rails.

Rails come in 6' lengths and include an off-white paintable cover. Like the CRE, the CRJ can be joined for seamless coverage over longer spans by using alignment pins for connecting adjoining rails. CRJ end caps can be purchased separately. (CRJEC)

Installation

*note: detailed installation instructions included with purchased railing

Step 1

Determine and mark the desired location for your rail. For best results use a level. Drill holes for screws based on stud location (minimum placement every 18"). Attach the railing to your wall with appropriate hardware, depending on wall type (see Figure 1).

Step 2

Connect railing with provided joint pins (see Figure 2).

Step 3

Once railing is installed on the wall, fit the plastic cover over the top. Press firmly until the cover snaps into place (see Figure 3).

Step 4

If desired, attach optional end cap (sold separately) and paint the plastic cover to match your wall color.

Figure 1




Figure 2




Figure 3




Figure 4

