

## TF32TUR



### °TF32TUR

TF32TUR is a bottom tensioning rail clip for the CRB/CRC or MH Rail system. TF32TUR provides the option of an angled installation from the CRB/CRC or MH Rail system. Simply twist the body of this tensioner and it draws in the cable. The TF series was designed with a teflon washer to prevent cable twisting. The side exit allows for extra adjustability. Excess cable can be trimmed (Re-seal cable ends using Arakawa's cable cutting kit, part # CCK-R)

### ° Product Information

#### cable size

1/16" 1.5 mm

3/32" 2.5 mm

2-3

#### maximum weight

1/16": 65 lbs. 30 kg

3/32": 155 lbs. 70 kg

#### function

Tensioner, U joint, side exit, for CRB/CRC or MH rail

#### installation instructions

Push fixture into CRB/CRC or MH rail, twist 90°, then tighten to fix TF32TUR into place. Loosen tensioner from base about one inch. Insert cable; turn tensioner down by hand.

#### Arakawa Hanging Systems

2505 SE 11th Avenue, Suite 122

Portland, Oregon 97202

phone: 503.236.0440

fax: 503.236.0427

toll free: 888.272.5292

[www.arakawagrip.com](http://www.arakawagrip.com)

Copyright © 2008 Arakawa & Co., Ltd. All rights reserved.  
Arakawa products are covered by U.S. and foreign patents, issued and pending. Specification and price change privileges reserved.

